

Collapsible Bulk Container

XYTEC® 4840 with Gemini sidewalls

Engineered of FDA approved high density polyethylene (HDPE) structural foam, the Gemini features proprietary TwinWall™ technology that is ridged and easy to clean. The TwinWall™ technology yields an optimum strength to weight ratio and unrivaled performance at 2500 lbs. loading capacity, making Gemini a strong, heavy-duty container fit to handle the toughest of material handling needs.

The Gemini works very well as a point of sale display used by major retailers for fruits and vegetables such as cantaloupes, honeydews and watermelons, etc. Backed with the strongest warranty in the industry, the Gemini system increases profitability by delivering improvements in productivity, storage/transport, hygiene, working environment and waste reduction.



SMOOTH & EASY TO CLEAN

The Gemini's smooth surface design and gentle radius transitions facilitate cleaning and ensure a sanitary container for repeat use. It is ideal for the food and meat industries in which hygiene is a critical factor. The Gemini has approximately 80% less surface to clean than ribbed containers.



ERGONOMIC HAND GRIPS

Convenient hand holds are molded on each side of the Gemini walls, making it effortless to erect the container quickly.

CG4840

The CG4840 features an industry standard C base and high-performance Gemini TwinWall sidewalls. Its internationally accepted 48" x 40" footprint cubes out truck trailers/international shipping containers and is compatible with rack storage systems. The smooth walls are easy to clean to assure a sanitary container for repeat use.

Height Option: 39"

Standard Colors: Grey/Black

Access Openings:

1, 2, 3 or 4 Access Doors (solid or vented) on 48" sides and/or 40" sides



CG484030
w/ 2 Access Doors



SG484030
w/ Solid Walls



SG484030
w/ 2 Access Doors

SG4840

The SG4840 features our high-performance SC base and Gemini TwinWall sidewalls. Its smooth walls and self-draining hinge pockets assure a sanitary container for repeat use. The SG4840 collapses to 1/3 of its original height and is ideal for hygiene sensitive industries such as food, meat and poultry processing.

Height Option: 39"

Standard Colors: Grey/Black

Access Openings:

1, 2, 3 or 4 Access Doors (solid or vented) on 48" sides and/or 40" sides

COLLAPSIBLE BULK CONTAINER

CG4840 & SG4840 SPECIFICATIONS

	CG484039	SG484039	LID: LS484003
OUTSIDE DIMENSIONS* Inch (mm)			
LENGTH	47.5 (1207)	47.4 (1204)	48.5 (1232)
WIDTH	39.4 (1001)	39.4 (1001)	40.3 (1024)
HEIGHT	39.3 (998)	39.4 (1001)	2.9 (74)
HEIGHT NESTED	38.6 (980)	38.6 (980)	-
FOOT INTERLOCK	0.7 (18)	0.8 (20)	-
INSIDE DIMENSIONS* Inch (mm)			
LENGTH	44.3 (1125)	44.2 (1123)	47.9 (1217)
WIDTH	36.2 (919)	36.2 (919)	39.8 (1011)
HEIGHT	32.8 (833)	32.8 (833)	2.0 (51)
FILL LINE	31.5 (800)	32.0 (813)	-
DOME HEIGHT††	0 (0)	0.48 (12)	-
COLLAPSED HEIGHT* Inch (mm)	15.2 (386)	15.4 (391)	-
COLLAPSED HEIGHT NESTED* Inch (mm)	14.5 (368)	14.6 (371)	-
COLLAPSED HEIGHT STACKED* Inch (mm)	102.2 (2596) 7 High	103.0 (2616) 7 High	-
ACCESS DOOR OPENING‡ Inch (mm)			
HEIGHT 48" side	15.0 (381)	15.0 (381)	-
WIDTH 48" side	31.0 (787)	31.0 (787)	-
HEIGHT 40" side	15.0 (381)	15.0 (381)	-
WIDTH 40" side	21.8 (554)	21.8 (554)	-
FORK OPENINGS Inch (mm)			
HEIGHT both sides	4.0 (102)	3.8 (97)	-
WIDTH 48" side	13.1 (333)	13.0 (330)	-
WIDTH 40" side	11.1 (282)	11.0 (279)	-
TARE WEIGHT** lbs (kg)			
			21.8 (9.9)
W/ SOLID SIDEWALLS	130.9 (59.4)	142.4 (64.6)	-
W/ 2 ACCESS DOORS 48" side	136.3 (61.8)	147.9 (67.1)	-
W/ 2 ACCESS DOORS 40" side	135.1 (61.3)	146.7 (66.5)	-
W/ 4 ACCESS DOORS	140.6 (63.8)	152.1 (69.0)	-
PROJECTED FOOTING AREA ††† sq ft	13.0 (1.2)	13.0 (1.2)	-
CONTAINER CAPACITY*** lbs (kg)	2500 (1134)	2500 (1134)	-
MAX. STATIC VERTICAL LOAD*** lbs (kg)	13148 (5963.3)	13148 (5963.3)	-
MAX. LOADED STACK*** lbs (kg)			
STATIC	6 High	6 high	-
DYNAMIC	2 High	2 high	-
VOLUME †††† sq ft			
EXTERNAL VOLUME	42.6 (1.2)	42.6 (1.2)	-
INTERNAL VOLUME	30.4 (0.9)	30.4 (0.9)	-
INTERNAL VOLUME TO FILL LINE	29.2 (0.8)	29.6 (0.8)	-
APPROX. RETURN RATIO	2.6:1	2.6:1	-
TRUCKLOAD QUANTITY collapsed/collapsed+ids/upright			
45 FT TRAILER	182/156/52	182/156/52	-
48 FT TRAILER	196/168/56	196/168/56	-
53 FT TRAILER	210/180/60	210/180/60	-
SEA CONTAINER CAPACITY collapsed/collapsed+ids/upright			
20 FT	60/50/20	60/50/20	-
40 FT	120/100/40	120/100/40	-
40 FT HIGH CUBE	140/120/40	140/120/40	-
FUNCTIONAL TEMPERATURE	-20°F to 120°F (-29°C to 49°C)		

*, **, ***, † and †† : see page 38 for specification disclaimers
LS = Structural Foam HDPE