

# Collapsible Bulk Container

## XYTEC® 4840 with standard sidewalls

There is no other container on the market as versatile as the Xytec 4840 collapsible container. Available in 34" and 39" heights, the award-winning Xytec 4840 can be used in a wide array of applications. The low tare weight of the Xytec 4840 deals with even the heaviest of material handling tasks. Its standard internationally-accepted 48" x 40" footprint cubes out truck trailers/international shipping containers and is compatible with rack storage systems, translating into efficient use of space and significant cost savings.



### C4840

Featuring standard sidewalls and standard C base, the C4840 was designed to handle a wide array of material handling applications. Low tare weight and high performance makes the C4840 container a popular choice in the material handling industry.

*Height Options: 34"/39"*

*Standard Colors: Grey/Black*

*Access Openings:*

*1 or 2 Access Doors on 48" sides*

### SC4840

Computer designed using the latest state-of-the-art CAD technology, the SC4840 features standard sidewalls and the superior performance SC base with replaceable fork straps to handle tougher material handling needs.

*Height Options: 34"/39"*

*Standard Colors: Grey/Black*

*Access Openings:*

*1 or 2 Access Doors on 48" sides*



### RACKING COMPATIBILITY

Several features make the Xytec 4840 container an excellent choice for racking systems:

- standard footprint size
- base edges that slide on support rails
- base free of center foot for unobstructed handling



### THE SC BASE

The SC base features

- a smooth exterior design for ease of cleaning
- replaceable fork strap system lowers maintenance costs
- strong 2500 lbs. loading capacity



C484034  
w/ 2 Access Doors



C484039  
w/ 2 Access Doors



SC484039  
w/ 2 Access Doors



SC484034  
w/ 1 Access Door

COLLAPSIBLE BULK CONTAINER

## C4840 & SC4840 SPECIFICATIONS

	C484034	C484039	SC484034	SC484039	LID: LS484003
<b>OUTSIDE DIMENSIONS* Inch (mm)</b>					
LENGTH	47.5 (1207)	47.5 (1207)	47.4 (1204)	47.4 (1204)	48.5 (1232)
WIDTH	39.5 (1003)	39.5 (1003)	39.4 (1001)	39.4 (1001)	40.3 (1024)
HEIGHT	34.1 (866)	39.5 (1003)	34.3 (871)	39.7 (1008)	2.9 (74)
HEIGHT NESTED	33.4 (848)	38.8 (986)	33.5 (851)	38.9 (988)	-
FOOT INTERLOCK	0.7 (18)	0.7 (18)	0.8 (20)	0.8 (20)	-
<b>INSIDE DIMENSIONS* Inch (mm)</b>					
LENGTH	44.3 (1125)	44.3 (1125)	44.2 (1123)	44.2 (1123)	47.9 (1217)
WIDTH	36.2 (919)	36.2 (919)	36.2 (919)	36.2 (919)	39.8 (1011)
HEIGHT	27.3 (693)	32.7 (831)	27.5 (699)	32.9 (836)	2.0 (51)
FILL LINE	26.6 (676)	32.1 (815)	26.7 (678)	32.1 (815)	-
DOME HEIGHT††	0 (0)	0 (0)	0.48 (12)	0.48 (12)	-
COLLAPSED HEIGHT* Inch (mm)	15.2 (386)	15.2 (386)	15.4 (391)	15.4 (391)	-
COLLAPSED HEIGHT NESTED* Inch (mm)	14.5 (368)	14.5 (368)	14.6 (371)	14.6 (371)	-
COLLAPSED HEIGHT STACKED* Inch (mm)	102.2 (2596) 7 High	102.2 (2596) 7 High	103.0 (2616) 7 High	103.0 (2616) 7 High	-
<b>ACCESS DOOR OPENING* Inch (mm)</b>					
HEIGHT 48" side	13.7 (348)	16.5 (419)	13.7 (348)	16.5 (419)	-
WIDTH 48" side	31.3 (795)	31.3 (795)	31.3 (795)	31.3 (795)	-
<b>FORK OPENINGS Inch (mm)</b>					
HEIGHT both sides	4.0 (102)	4.0 (102)	3.8 (97)	3.8 (97)	-
WIDTH 48" side	13.1 (333)	13.1 (333)	13.0 (330)	13.0 (330)	-
WIDTH 40" side	11.1 (282)	11.1 (282)	11.0 (279)	11.0 (279)	-
<b>TARE WEIGHT** lbs (kg)</b>					
W/ SOLID SIDEWALLS	117.0 (53.0)	132.0 (59.9)	126.5 (58.3)	142.1 (64.5)	-
W/ 2 ACCESS DOORS	120.0 (54.4)	133.4 (60.5)	131.5 (59.6)	143.5 (65.1)	-
PROJECTED FOOTING AREA m <sup>2</sup> (sq ft)	13.0 (1.2)	13.0 (1.2)	13.0 (1.2)	13.0 (1.2)	-
CONTAINER CAPACITY*** lbs (kg)	2500 (1134)	2500 (1134)	2500 (1134)	2500 (1134)	-
MAX. STATIC VERTICAL LOAD*** lbs (kg)	13080 (5933)	13148 (5963.8)	13080 (5933)	13148 (5963.8)	-
<b>MAX. LOADED STACK*** lbs (kg)</b>					
STATIC	6 high	6 high	6 high	6 high	-
DYNAMIC	3 high	2 high	3 high	2 high	-
<b>VOLUME m<sup>3</sup> (cu ft)</b>					
EXTERNAL VOLUME	37.0 (1.0)	42.9 (1.2)	37.1 (1.1)	42.9 (1.2)	-
INTERNAL VOLUME	25.3 (0.7)	30.3 (0.9)	25.5 (0.7)	30.5 (0.9)	-
INTERNAL VOLUME TO FILL LINE	24.7 (0.7)	29.8 (0.8)	24.8 (0.7)	29.7 (0.8)	-
APPROX. RETURN RATIO	2.3:1	2.6:1	2.3:1	2.6:1	-
<b>TRUCKLOAD QUANTITY collapsed/collapsed+hdg/upright</b>					
45 FT TRAILER	182/156/78	182/156/52	182/156/78	182/156/52	-
48 FT TRAILER	196/168/84	196/168/56	196/168/84	196/168/56	-
53 FT TRAILER	210/180/90	210/180/60	210/180/90	210/180/60	-
<b>SEA CONTAINER CAPACITY collapsed/collapsed+hdg/upright</b>					
20 FT	60/50/20	60/50/20	60/50/20	60/50/20	-
40 FT	120/100/40	120/100/40	120/100/40	120/100/40	-
40 FT HIGH CUBE	140/120/60	140/120/40	140/120/60	140/120/40	-
FUNCTIONAL TEMPERATURE	-20°F to 120°F (-29°C to 49°C)				

\*, \*\*, \*\*\*, † and †† : see page 38 for specification disclaimers  
LS = Structural Foam HDPE